



- DRAWING NOTES:**
1. CAMERA SHALL BE INSTALLED, MOUNTED SHALL BE ELECTRICALLY OPERATED, PEDAL MOUNTED FROM CURB AT BASE AND ANCHOR BOLT PLACEMENT WITH WALL CONSTRUCTION. CAMERA HOUSING SHALL BE 1/2" ABOVE ELEVATION AT ENTRANCE GATE.
 2. LOCATE CAMERA AT LEVEL TWO FLOOR ELEVATION.
 3. FIELD COORDINATE EXACT LOCATION OF CAMERA.
 4. COORDINATE TRANSFER CASE MEASUREMENTS AND CONNECTIONS WITH BLANKET INSTALLER FOR ALL GND MOUNTED DEVICES.
 5. CONNECT MOTORIZED CONTROL FOR GARAGE DOOR TO DOOR RELEASE SYSTEM SO THAT ONLY ONE DOOR CAN BE OPEN AT ANY GIVEN TIME.

2 | SECURITY LEVEL ONE PART PLAN
 ES-101 | SCALE: 1/8" = 1'-0"

1 | SECURITY LEVEL ONE FLOOR PLAN
 ES-101 | SCALE: 1/8" = 1'-0"

SEE 1 FOR CONTINUATION (ES-101)

SEE 2 FOR CONTINUATION (ES-101)